

(12)

(21) **2 285 645**

(51) Int. Cl.⁶: **H04H 009/00, H04N 007/173**

(22) **05.01.1998**

(85) **10.06.1999**

(86) **PCT/US98/00091**

(87) **WO98/31114**

(30) **08/779306 US 06.01.1997**

(72) **GRAUCH, EDWARD ROWLAND (US).
DANNER, FRED THOMAS III (US).
BATTEN, JOHN CHRISTOPHER (US).**

(71) **BELLSOUTH INTELLECTUAL PROPERTY
CORPORATION,
1155 Peachtree Street, N.E., ATLANTA, XX (US).**


(74) **Bereskin & Parr**

(54) **PROCEDE ET SYSTEME DE SUIVI DE L'UTILISATION DES RESEAUX**

(54) **METHOD AND SYSTEM FOR TRACKING NETWORK USE**



(72) GRAUCH, EDWARD ROWLAND, US
(72) BATTEN, JOHN CHRISTOPHER, US
(72) DANNER, FRED THOMAS III, US
(71) BELL SOUTH INTELLECTUAL PROPERTY CORPORATION, US
(51) Int. Cl.⁶ H04H 9/00, H04N 7/173
(30) 1997/01/06 (08/779306) US
(54) **PROCEDE ET SYSTEME DE SUIVI DE L'UTILISATION DES RESEAUX**
(54) **METHOD AND SYSTEM FOR TRACKING NETWORK USE**



(57) La présente invention concerne un procédé et un système de suivi de l'utilisation d'un réseau par les abonnés, en particulier du réseau de fourniture de supports interactifs fournissant de la programmation à des coffrets de raccordement couplés à des appareils d'affichage. Ce système fait le suivi d'événements, y compris les changements d'état du coffret découlant d'un changement de programmation ou de canal, ou découlant d'une mise en service par l'abonné et de l'interaction avec une application particulière de services interactifs. Chaque application crée un article événement comprenant l'identificateur d'application, l'événement

(57) A method and system for tracking subscriber use of a network, such as an interactive media delivery network, which delivers programming to set top boxes coupled to a display device is disclosed. The system tracks events, including any change in status of a set top box caused by a change in programming or channel or a subscriber's activation and interaction with a particular interactive services application. Each application forms an event record comprising the application ID, event and time stamp. Collected event records are buffered, compressed, formed into packets and transmitted to a merge processor that combines event records with





(21) (A1) **2,285,645**
(86) 1998/01/05
(87) 1998/07/16

et le groupe date-heure. Le procédé consiste alors à prendre les articles événement, à les ranger en mémoire tampon, à les comprimer, à les rassembler en paquets, et à les transmettre à un processeur de fusion qui combine les articles événement aux données de contenu décrivant le contenu de programmation distribué par le réseau. Les articles événement et les données de contenu sont fusionnés de façon à former pour chaque coffret de raccordement d'abonné des calendriers d'événements qui montrent l'activité abonné ou la programmation restituée au profit d'un utilisateur pendant une période de temps déterminée.

content data that describes the programming content distributed throughout the network. The event records and content data are merged to form event timelines for each subscriber's set top box that show subscriber activity or programming played to a subscriber over a selected time period.



PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04H 9/00, H04N 7/173	A1	(11) International Publication Number: WO 98/31114 (43) International Publication Date: 16 July 1998 (16.07.98)
--	----	---

(21) International Application Number: PCT/US98/00091

(22) International Filing Date: 5 January 1998 (05.01.98)

(30) Priority Data:
08/779,306 6 January 1997 (06.01.97) US

(71) Applicant: BELLSOUTH CORPORATION [US/US]; 1155 Peachtree Street, N.E., Atlanta, GA 30309-3610 (US).


(72) Inventors: GRAUCH, Edward, Rowland; 825 Kings Court, Atlanta, GA 30306 (US). BATTEN, John, Christopher; 720 Cambridge Crest Lane, Alpharetta, GA 30202 (US). DANNER, Fred, Thomas, III; 2850 Lakewind Court, Alpharetta, GA 30202 (US).

(74) Agents: PRATT, John, S. et al.; Kilpatrick Stockton LLP, Suite 2800, 1100 Peachtree Street, Atlanta, GA 30309-4530 (US).

(81) Designated States: AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GE, GM, GW, HU, ID, IL, IS, JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, SL, TR, TT, UA, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published*With international search report.***(54) Title:** METHOD AND SYSTEM FOR TRACKING NETWORK USE**(57) Abstract**

A method and system for tracking subscriber use of a network, such as an interactive media delivery network, which delivers programming to set top boxes coupled to a display device is disclosed. The system tracks events, including any change in status of a set top box caused by a change in programming or channel or a subscriber's activation and interaction with a particular interactive services application. Each application forms an event record comprising the application ID, event and time stamp. Collected event records are buffered, compressed, formed into packets and transmitted to a merge processor that combines event records with content data that describes the programming content distributed throughout the network. The event records and content data are merged to form event timelines for each subscriber's set top box that show subscriber activity or programming played to a subscriber over a selected time period.



METHOD AND SYSTEM FOR TRACKING NETWORK USE

This invention is a method and system for tracking subscriber use of network applications, particularly network applications involving delivery of interactive media or video programming.

BACKGROUND OF THE INVENTION

Broadcast and cable television have long dominated the visual media market. New communications technologies, however, have accelerated demand for new types of media such as video on demand, interactive video, interactive gaming, home shopping or interactive advertising. Unlike broadcast television, viewers of these services typically are paying "subscribers," although payments from advertisers also pay a large share of the costs of providing these media services.

To gauge the effectiveness of their spending, advertisers have long sought information on viewers' viewing patterns. A number of devices and techniques exist for gathering such information. For instance, U.S. Patent Nos. 4,258,386 to Cheung and 4,556,030 to Nickerson, et al., describe the general concept of deploying in viewers' homes devices for monitoring a viewer's television set ("TV") in order to accumulate data illustrating viewing habits such as which channels were watched at particular times. Accumulated data is then forwarded via telephone lines to a central location for analysis. Cheung sends data from particular monitoring stations at a preselected, specific "window" of time; interruptions to transmission during that window result in the Cheung system forwarding the data at another time.

Other systems and methods provide somewhat more use data than just channel numbers viewed and time of viewing. Typically, however, the information is for a smaller subset of users. Thus, U.S. Patent Nos. 4,816,904 to McKenna, et al., 4,912,552 to Allison, III, et al. and 5,374,951

to Welsh, all disclose monitoring "panelist" TV use in order to collect data about panelist viewing patterns as well as certain marketing information. Generally, panelist monitoring is used to gauge the effectiveness of advertising on selected groups of "panelists," each of which is one
5 household in a group comprising a "panel," typically located in a particular geographical area.

Monitoring not only determines which commercial and TV programs the panelist views but also may be used to gather information about which products panelists purchase. For instance, the U.S. patent to McKenna
10 discloses a remote data collection unit located at a panelist home that monitors viewer identification data and TV functions (e.g., channel viewed, VCR viewing time or game time). Additionally, a wand is provided for inputting bar codes of purchased items. Monitored data is sent via the telephone network to a central location, which can also download
15 questionnaires to the panelist and receive responses. Allison and Welsh disclose similar monitoring systems and methods. Instead of simply monitoring the channel number that a panelist was viewing at a particular time, Welsh discloses monitoring identification information carried in the television signal vertical blanking interval that identifies preselected
20 commercials. After detecting and storing the identification information that identifies particular commercials viewed by panelists, the data is transmitted by telephone to a central location for analysis.

Monitoring systems also have been used with some early interactive media systems. U.S. Patent No. 5,404,393 to Remillard discloses an
25 interactive TV system. Among other elements of the system, a controller monitors TV channels and time/date stamps the selected channel so that, indirectly, viewers' programming choices may be monitored. Data is assembled into a "user profile," which is uploaded to an appropriate facility via the telephone network.

Nevertheless, while panelist monitoring systems like those of Allison, McKenna and Welsh or interactive television monitoring systems like Remillard's provide somewhat more monitoring data than just TV tuning data, they do so only for limited groups. For example, when more data is gathered (like purchase information), it is done only for the panelist groups, rather than for subscribers to the entire system. Also, systems like McKenna's that uses a wand for scanning bar codes are intrusive systems that require user action to collect data rather than collecting data passively and automatically. Other systems contemplate capturing only some of the data generated by subscriber's viewing activities or only some of the ratings information. For instance, previous systems typically capture ratings information that identify television shows viewed rather than whether the subscriber viewed commercials displayed during those shows.

Perhaps more importantly, none of the systems described attempt to match "raw" information on channels viewed with programming information. Nor do those systems match viewing pattern information with demographics information about the particular users in order to provide more "targeted" advertising.

SUMMARY OF THE INVENTION

The present invention uses a collector, associated with a subscriber's set top box ("STB"), to obtain data about any "events" -- subscriber actions or changes in programming -- that are of interest. Data about virtually any events, from channels watched to volume changes to interactive applications invoked, may be captured with the collector. Event records comprising such data, as well as the identity of the application involved and the event time, are buffered. Periodically or on command, event records are uploaded from the buffer to a merge processor such as through an interactive network that allows for duplex communication with the STB. The merge processor, which may be a head end server or a workstation computer forming part of or coupled to the media delivery network, receives

(1) the event data and (2) content data that identifies programming content broadcast or delivered throughout the region in which the system is deployed. Timelines showing particular events over time may then be generated for each subscriber. Rather than just determining the channel
5 viewed and time of day, the event timelines describe the programming or interactive applications selected by or shown to a subscriber over a selected period of time (e.g., 24 hours).

The merge processor may further filter this collected and merged data to generate reports ranging from descriptions of a single user's viewing
10 patterns to very high level viewing patterns showing the number of users who watched or participated in a particular program for a selected time period. Further, that information can be combined with billing and demographics information to provide detailed information on a particular subscriber's or group of subscribers' viewing and related buying patterns.

15 The present invention thus involves a method for obtaining detailed information on every application invoked by a subscriber and information about the type of programming shown. The first step is to identify data that describe the events of interest that occur. Those events include: the channel viewed, a switch to another channel, a passive change in
20 programming because of a commercial break or change to a new program, use of a VCR or other ancillary device, or invocation of an interactive application and subscriber commands given to the system during the application. Event data also includes start and stop times, identification of the subscriber's STB or specific data needed to be recorded for any
25 particular interactive or other application.

Event records are formed from this collected data and buffered before uploading through the interactive or other media delivery network to a headend, server or third party data analysis system. Before uploading, the captured data may be compressed and formed into packets for
30 transmission.

Using the system or method of the present invention allows service providers to obtain ratings information and detailed information on subscriber viewing patterns and subscriber use of interactive applications. Thus, the present invention can track the number of subscribers viewing or
5 watching particular programs, including advertisements. It also can track use of particular interactive applications such as video on demand. The invention automatically matches data describing programming content with event data describing a channel or application activated or controlled by the subscriber. This allows the invention comprehensively to track user
10 "channel surfing." Also, the invention can compare subscriber demographics or billing information with viewing pattern information in order to tailor commercials to those subscribers; determine whether subscribers with a selected demographic background viewed a commercial of interest; or determine the demographics of subscribers that viewed selected
15 commercials.

Persons skilled in the art will recognize that the present invention may be used with numerous types of networked media delivery systems. For instance, the method or system of the present invention can be deployed on an interactive media delivery system or modified for use with a conventional
20 cable television network, a wireless cable television network, or a home satellite television network.

It is accordingly an object of the present invention to provide a system and method for collecting information about patterns of subscriber viewing and use of a media delivery system.

25 It is another object of the present invention to provide a system and method for determining which network applications, particularly interactive applications, are invoked by particular subscribers.

It is an additional object of the invention to provide a system and method for communicating collected information to a merge processor.

It is a further object of the invention to provide to the merge processor information about the programming content distributed over the media delivery system.

It is yet another object of the invention to provide a system and
5 method for merging the collected information with the programming information in order to obtain comprehensive information about programming shown to or network applications invoked by subscribers. Other objects, features and advantages of the present invention will become apparent upon reading the rest of this document.

10

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a block diagram of elements of one embodiment of the system of the present invention.

Figure 2 shows a block diagram of a Set Top Box as used with the
15 embodiment of the present invention shown in Figure 1 and provided with a clickstream processor.

Figure 3 shows a schematic diagram showing the upload cycle for collected event data.

Figures 4A and 4B show the upload of collected event data from a
20 selected Set Top Box through the network to the staging server shown in Figures 1 and 5.

Figure 5 shows an overview of the staging server, its functions and its interconnections with various data sources.

Figure 6A shows the system elements required for merging and
25 parsing the event and content data collected by the present invention.

Figure 6B shows the assignment of priority to content data necessary for completing the merge and parse process.

Figure 7 shows the results of a merge and parse process of the
30 present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

System Overview

Figure 1 shows a block diagram of the components of the system 20. System 20 is a demographics and programming ratings collection and analysis system that may be deployed for use on an interactive media delivery system such as the Interactive Video Services Network deployed by BellSouth Interactive Media Services. That interactive system is described in co-pending application S/N 08/428,718, assigned to the assignee of the present invention and which document is hereby incorporated in its entirety by this reference. However, persons skilled in the art will recognize that the present invention may be used with any of a variety of interactive media delivery systems, standard or wireless cable television systems, satellite television systems or other media delivery systems that allow duplex communication (perhaps with the return path via a separate (e.g., telephone) network) to a set top box ("STB") 30 coupled to a subscriber's display device, such as a television set or the like.

In any event, Figure 1 shows various system 20 elements and subsystems that communicate with each other to transmit collected information, data error detection schemes and data acknowledgments. Briefly, the STB 30 communicates through a distribution network 52 with a video server 60, such as a video transfer engine ("VTE"), that may be acquired from Hewlett Packard ("HP"), with a video/object storage database 54. Video server 60 couples to a video control server 56, such as an Inter Media Server available from Sybase and deployed on a platform such as an HP 9000, with a database 58. The video server control 56 controls video server 60 and also logs information about video server 60 use. A staging server 70 receives collected records of events of interest. These "event records" pass through the video server control 56, which also couples to a Marketing and Information System ("MKIS") 100 that couples to staging server 60, which receives (1) the event records and (2) content data from

various sources 120, 140 and 160 identified in Figure 1 and which describe programming content available through the interactive network to all subscribers. MKIS 100 may be coupled to a third party search and analysis system 110 that can provide customer support operations.

5 STB 30 provides a platform by which (1) content is converted to a selected video format (e.g., NTSC or PAL) and presented to the subscriber or (2), for interactive systems, messages are exchanged (including video data) over a network 52 with the staging server 70. STB 30 also could include platforms capable of: (1) receiving messages from a user input
10 device, such as a hand-held remote control unit; (2) translating video signals from a network-native format into a format that can be used by the television or display device; (3) inserting alphanumeric or graphical information into the video stream in order to "overlay" that information on the video image; (4) providing graphic or audio feedback to a user; or (5) possibly the most basic
15 function, simply routing a traditional broadcast signal to a viewing device connected to the STB 30. Analogous terms to STB include: Set-Top Terminal ("STT"), Cable Converter, and Home Communications Terminal ("HCT") and any of these devices may be coupled to or made a part of a display device for showing programming to subscribers. Generally, STB 30
20 may be a Richmond or 8600X available from Scientific Atlanta, a CFT 2200 available from General Instruments, Thomson's DSS or any other device equipped with (1) a microprocessor; (2) memory for operating instructions and storage; and (3) a control interface for accepting subscriber commands from a remote control device or control panel.

25 For the particular embodiment of system 20 shown in the Figures, collected event records that are packaged for transport through system 20 are called "clickstream" data or information. Figure 2 shows a clickstream processor 34 that resides in the memory, such as DRAM or the like, of an STB 30 and which has a clickstream kernel 36, buffers 42 or 44, a

clickstream upload handler 40, a clickstream controller 38 and a clickstream event API (application programming interface) 41.

Briefly, the clickstream kernel 36 buffers events passed to it by various network applications through the clickstream event API 41.

5 Clickstream controller 38 accepts control messages from staging server 70 and appropriately stores their payload. Typical messages may be sent over the Extended Super Frame ("ESF") pass-through data link and control the uploading of clickstream data. Clickstream upload handler 40 accepts control messages over the system 20, which messages control the
10 uploading of collected clickstream data over the reverse path through network 52. Also, the clickstream upload handler 40 stores the payload of these messages in appropriate and available memory and accepts the messages sent to it to acknowledge the receipt of uploaded clickstream data.

15 Referring again to Figure 1, video server 60 provides information from video/object storage 54 to the particular interactive system over which system 20 is deployed. Clickstream data collected at STBs 30 can be uploaded to staging server 70 in any number of ways. For instance, Figure 1 shows that the distribution network 52 could couple directly to staging server
20 70, allowing clickstream data packets sent from STBs 30 to be forwarded to staging server 70 directly and for staging server 70 to then return via the network 52 data acknowledgments. A network management controller 50 controls the flow of information through the network 52. Alternatively, Figure 1 and, in greater detail, Figure 4B, show that clickstream data packets
25 may be sent to the distribution network 52 to the video server 60. Video server 60 passes through both clickstream data uploads from various STBs 30 and data acknowledgments returned to the STBs 30. A communications router inside the video server 60 redirects traffic to the appropriate destination. Video server control 56 similarly acts as a pass-through device
30 for STB 30 clickstream data going to the staging server 70 and as a pass-

through device for staging server 70 data acknowledgments to the STBs 30. Also, video server control 56 may provide log information that identifies interactive applications invoked by particular STBs 30. That log information is provided to the staging server 70 so that video server control 56 also acts
5 as another data source about content available over the network, like EPG metadata source 120, broadcast advertising metadata source 140, or advertising traffic control metadata source 160. Staging server 70 collects all such clickstream data and content data, analyzes and then forwards it to MKIS database 100 or to a third-party analysis engine and database 110, as
10 described in more detail in the text associated with Figures 5-7.

Journaling of Event Data

Clickstream processor 34 collects information to create a "journal" or log about all events or selected events of interest. An event is an action or a change in the state of a STB 30 that is deemed important to building a
15 knowledge base on subscribers or their viewing patterns. For example, an event can include key presses to change channels or volume, mute, to enter the navigator for the interactive system, to turn the STB 30 off or on, to fast forward, to pause or to rewind a video obtained via the video on demand application. The events include applications called by the subscriber, such
20 as interactive gaming applications, an electronic program guide, a video on demand or near video on demand application, a home-shopping application or a particular company's interactive application, such as The Weather Channel's weather on demand, World Span's travel on demand or Light Span's educational interactive application. Events include subscriber use of
25 and control commands to peripheral devices coupled to the STB 30 or a subscriber's display device, such as a VCR or videodisk player.

Each application residing on the STB 30 interfaces with the clickstream processor 34 to send selected data for maintaining a desired journal. Assuming that the system 20 is used with an interactive system,
30 many different applications may be deployed over that system and may be

triggered by the subscriber. Some fairly typical applications that might be invoked include:

- a cable television application that handles subscriber remote controls (like channel or volume changes);
- 5 • an electronic programming guide application such as TV Data, Prevue or Star Sight interactive services;
- an interactive game;
- a video on demand or near video on demand application;
- company specific applications, that might be offered by content
10 provider such as the Weather Channel, MTV, Showtime, etc.; or
- a navigator application to help the user choose options.

Each of these applications, as well as some internal applications that the system 20 may wish to monitor, will be assigned a unique application identifier.

- 15 Clickstream processor 34 interfaces with the various applications resident in the STB 30's operating system 32 and any third party applications 33. Note that for systems using other types of STB 30's than the embodiment described in the Figures, those STB 30's need not have an operating system. Instead, all instructions can be written directly to the
20 memories of those particular STBs. Applications 33 can be added by either downloading entirely new software directly to memory or by downloading new tables as described below.

- When an application 33 reaches a point where an "event" of interest has been generated, the application 33 stores an event record to memory.
- 25 The application 33 then launches to the clickstream kernel 36 the event record, including information such as: (1) the application's 33 identification code (e.g., the "Cable Television Application" or a particular interactive application); (2) a count of the amount of information (number of bytes) to be journaled; (3) a "time stamp" that defines a unique point in time, e.g., by
30 defining the date and time of day, accurate to the hour, minute or second; (4)

an identification code for the event, or (5) where the event data was stored. Clickstream kernel 36 uses the information provided by the applications 33 to collect the event data, format it and place it into a buffer 42 or 44. Table I shows the type of information that will be generally sent by the clickstream processor 34 to the buffers 42 or 44.

Table I: Application Event Record		Size
Timestamp		6 bytes
Assigned Application ID		16 bits
Number Bytes to Follow (length)		8 bits
Application Specific Data with customized formats and lengths		Multiple Bytes

Global table II defines events of interest that each application can identify, collect, store in the "Application Specific Data" field and notify the clickstream kernel 36. These events could be as simple as a broadcast channel change by pressing the "Chan Up" remote key. All of these event types can be accessed and used by each application. While each application may not use every possible event type, the number of events available for collection allows system 20 to extract any pertinent usage information for analysis. Also, the use of the global table II increases system 20 efficiency because event types can be modified, added or removed.

Table II: EVENT DEFINITIONS	
Code	Event
Content Related Events	
0x0000	Passive Content Change
Direct Key Presses	
0x0001	TV <> ITV Pressed

Table II: EVENT DEFINITIONS	
Code	Event
Application/State Switching Related	
0x0028	AC Power ON
0x0029	Application Switch (Normal)
0x002A	Application Switch (Abnormal)

0x0002	Power Pressed
0x0003	One (1) Pressed
0x0004	Two (2) Pressed
0x0005	Three (3) Pressed
0x0006	Four (4) Pressed
0x0007	Five (5) Pressed
0x0008	Six (6) Pressed
0x0009	Seven (7) Pressed
0x000A	Eight (8) Pressed
0x000B	Nine (9) Pressed
0x000C	Zero (0) Pressed
0x000D	Channel Up Pressed
0x000E	Channel Down Pressed
0x000F	Volume Up Pressed
0x0010	Volume Down Pressed
0x0011	Last Channel Pressed

0x002B	Application Terminated (Normal)
0x002C	Application Terminated (Abnormal)
0x002D	Soft Power OFF
0x002E	Soft Power ON
0x002F	OFF State Polling Event
General	
0x0030	Direct Channel Change
0x0031	Mute
0x0032	Un-Mute
0x0033	Volume Change Below 50%
0x0034	Volume Change Below 25%
0x0035	Volume Change Below 10%
0x0036	Volume Change Above 50%
0x0037	Volume Change Above 25%
0x0038	Volume Change Above 10%
0x0039	Change to Interactive Mode
0x003A	Change to Broadcast Mode

Note that Table II defines relative volume changes (e.g. "volume change below 50%," "volume change below 25%," etc.). Although the applications could capture the actual key presses that lead to these relative volume changes, that level of detailed information is of little use to system operators. Also, capturing all that detail leads to more records and higher demands upon the transmission network 52 when those records are

uploaded. Applications could also be configured to "filter" other unwanted details about other subscriber activities. For example, when subscribers "channel surf" by quickly flipping through a number of channels in a short period of time, the application could be configured not to record channel changes unless the subscriber paused for greater than a certain selected time period (e.g., 15 to 30 seconds). Again, this eliminates information of little use and decreases network traffic.

Table III defines a small portion of a sample global channel identification table that proposes codes for identifying national and local broadcasters. Such a table allows any application journaling events which occur while subscribers are viewing broadcast or cable television programs to identify the network carrying the programming content by using a subset of the global table II. In this way channel lineups can be changed yet the identifier for a broadcast or cable network would stay the same. The use of this mapping scheme eliminates the need to map an ever-changing channel number to a network.

Table III: Broadcast Channel Identification	
0x0100 to	
0x011F	News/Talk Shows
0x0100	CNN
0x0101	Headline News
0x0102	The Weather Channel
0x0103	CNBC
0x0104	CSPAN
0x0105	CSPAN-2
0x0106	America's Talking
0x0107	Talk Channel
0x0108	Court TV
0x0109	The Crime

Table III: Broadcast Channel Identification	
0x0120 to	
0x013F	Sports
0x0120	ESPN
0x0121	ESPN-2
0x0122	SportSouth
0x0123	The Golf Channel
0x0124	Classic Sports Network
0x0125	Prime Network
0x0126	NewSport
0x0140 to	
0x015F	Music
0x0140	MTV

	Channel
0x010A	National Empowerment TV

0x0141	VH-1
0x0142	Country Music Television
0x0143	The Nashville Network
0x0144	The Box
0x0145	Video Jukebox
0x0146	MOR Music TV
0x0147	Music Choice

Table IV below shows some possible identification codes for particular applications. Note that each application could be programmed to insert its application ID code into the event record without accessing table IV. But by having each application access the table IV during the journaling process, the system's ability to modify or add application ID codes easily is enhanced because such codes could be populated across system 20 by downloading an updated table IV. Providing for downloading of new tables increases the application footprint and system 20 complexity so tables can also be part of the application programming.

Table IV: Application Identifiers	
ID Code	Content
0x0000	Operating System
0x0001-F	Operating System Sub-Systems
0x0010	Application Manager
0x0011	Cable Television Application
0x0012	Clickstream Kernel
0x0100	EPG System
0x0101	Digital Pictures - Interactive Game

0x0110-F	Viacom - MTV / Showtime, etc.
0x1000	Interplay Written Applications General ID
0x1001	Interplay Runtime Engine
0x1002	Interplay Navigator
0x1003	Interplay VOD
0x1004	Interplay NVOD
0x1005	Interplay TownGuide
0x1100	The Weather Channel, Weather On-Demand
0x1101	Worldspan - Travel On-Demand
0x1102	Lightspan - Educational Interactive Application
0xFFFF	Missed Events Record

Each particular application can simply reference the global application, event and channel identification tables (which periodically may be updated and then downloaded to STBs 30) in order to build an event record. Examples of application specific event records that may be created in this manner are shown in Tables V through VIII below and discussed in associated text.

A cable TV application 33 may tune analog or digital broadcast services. When a command to change channels is entered, the cable TV application 33 is invoked. The cable TV application 33 begins building an event record by inserting an application ID and time stamp into the record. Next, the application 33 determines the "event ID" by cross-referencing the command with the global event ID table II for the proper code. Then, the application 33 journals the "Channel ID."

Although the Channel ID could simply be the number of the channel, that information means little. The fact that channel 6 was watched more than channel 7 has little or no meaning unless networks and, ultimately, the content delivered by those networks are associated with particular channels. Accordingly, the Channel ID may be a field, like a 16 bit field, which uniquely

of the service provider's communication of name collect failure is shown in FIG. 2C at 160 and described above. Once this communication is sent 424, the service provider disconnects 426 and returns to idle mode 400.

If the service provider successfully completes the recording of the incoming
5 caller's response 428, the service provider communicates the completion to the mobile station 430 preferably using USSD. The mobile station's receipt of this communication is shown in FIG. 2C at 164. Once the communication is completed 430, the service provider returns to awaiting-commands mode 410.

As described above, during the mobile station's carrying out of the embodiment
10 of the present invention, the mobile station may signal the service provider to handle an unanswered call. This signalling is shown in FIG. 2C at 182 and is described above. Referring to FIG. 4A, if, while waiting for commands 410, the service provider preferably receives a USSD signal to handle an unanswered call 432 from the mobile station, the service provider initiates its handling of the unanswered call 434. The call is
15 then handled by the service provider 436. The service provider may record a voice message from the incoming caller. As seen in FIG. 4C, if the service provider is disconnected from the incoming caller for some reason 438, the service provider will stop handling the call 440 and will return to idle mode 400. Once the service provider completes its handling of the call 442 without a premature disconnection, the service
20 provider disconnects from the incoming caller and the mobile station 444 and returns to idle mode 400. The disconnection of the service provider by the mobile station 185 is shown in FIG. 2F.

As described above, during the mobile station's carrying out of the embodiment
of the present invention, the mobile station may signal the service provider to screen the
25 incoming caller. This signalling to screen 214 is shown in FIG. 2D and is described above. If, while waiting for commands 410, the service provider receives a USSD signal to initiating screening 446 from the mobile station, the service provider will play the screening message 448 for the mobile station. For example, the service provider the service provider plays and the mobile station receives the following message: "Hello,

[information provided by the caller] is holding. Would you like to accept the call?"

Then, the service provider starts a timer 450 designated herein as T3. Timer T3 is used to govern the amount of time the service provider will wait for the mobile station to accept or reject the incoming call. Preferably, the timer is set to expire in approximately
5 3-6 seconds.

Then, the service provider awaits the mobile station's response to the screening message 452. The service provider's receipt of the screening message and consequent communication to the service provider of the response is described above and is shown in FIGS. 2D and 2E.

10 If the service provider is disconnected for any reason while awaiting the mobile station's response 458, the service provider will stop the timer T3 460. Then, the service provider will return to idle mode 400.

If the timer T3 expires before the mobile station user's response to the screening message is received 454, then the service provider initiates handling of the incoming call
15 by the service provider 456. The unanswered incoming call is handled by the service provider in the manner described above and shown in FIG. 4C. For example, a voice message from the incoming caller to the mobile station user is recorded.

If a negative response, or a rejection, is received by the service provider from the mobile station 462, the service provider will stop the timer T3 464 and signal the mobile
20 station that the call was rejected 466. This signal is preferably accomplished using USSD. The mobile station's receipt of such a signal is shown in FIG. 2E at 236. After signalling the mobile station 466, the service provider will return to awaiting-command mode 410. In the normal situation, the subsequent command from the mobile station will be that the service provider handle the unanswered call (shown in FIG. 2E at 266).
25 In such a case, the service provider would carry out the necessary steps, beginning with the steps shown as 434 and 436 in FIG. 4A.

If an affirmative response, or an acceptance, is received by the service provider from the mobile station 468, the service provider will stop the timer T3 470. Next, the service provider signals the mobile station that the call was accepted 472 using USSD.

Rewind	0x03
Info (Help) Video or Screen Played	0x04
reserved	0x05
reserved	0x06
reserved	0x07

Table VIII below shows the event record for the Electronic Program Guide (EPG) application 33. The EPG application 33 records the application ID, timestamp and event ID records just as do the above applications described in tables V-VII. Additionally, it has an application 33 state ID field that identifies which of the display screens were accessed by subscribers, as shown below.

Table VIII: Electronic Program Guide (EPG) Application Event Record	Size/ Data
Application ID: See Application ID table IV	16 bits
Timestamp: Identifies event time	6 bytes
Event ID: See Global Event ID table for Syntax	16 bits
Application State ID: See below for information tracked:	8 bits
Initial Display Screen	0x00
Look Ahead Display 4 Hour	0x01
Look Ahead Display 8 Hour	0x02
Look Ahead Display 12 Hour	0x03
Look Ahead Display 16 Hour	0x04
Look Ahead Display 20 Hour	0x05
Look Ahead Display 24 Hour	0x06
Reserved	0x07

Generally, similar information about other applications 33, such as home shopping, interactive gaming or any other new applications deployed over an interactive or other media delivery system, can be tracked in a similar fashion. Additionally, the journaling process may be used to track errors within the system 20, with clickstream kernel 36 journaling such errors using the same method as described above.

Over time, the journaling needs of system 20, or system 20 itself may evolve. Applications may be changed or new ones deployed. New events may become of interest to the operator of system 20. In order to provide flexibility for system 20, operators may download to STBs 30 new or replacement applications that will include the necessary processes for journaling all events of interest.

Sample Journal

Assume that Mr. Smith turns on his interactive television at 7:30 p.m. to watch a half hour news program on channel 5, which corresponds to CNN for that region. At 8:00 p.m. he accesses the Navigator application to order a video through the video on demand application. He then accesses the Video on Demand application, which automatically begins playing a video at 8:04, pauses the video at 8:50 and begins playing again at 8:55 until it is completed at 9:45, at which point he turns off his interactive TV.

Mr. Smith's activities generate the following event records shown in table IX below (for convenience, multiple events occurring under a single application are grouped even though separate records are created in operation):

Table IX: Sample Event Records	
Cable Application Event Record 1 Content	Data
Application ID: See table IV for application ID Code	0x0011
Timestamp: Identifies event time	1/1/96 7:30:01 p.m.
Event ID: See Global Event ID table II to retrieve code for "power pressed"	0x002
Cable Application Event Record 2 and 3 Content	Data
Application ID: See table IV for application ID Code	0x0011
Timestamp: Identifies event time (Date will be same for second entry)	1/1/96 7:30:03 p.m.; 8:00:01 p.m.
Event ID: See (1) global Broadcast Channel ID table III to determine that Channel 5 is CNN and locate code and (2) table II for an event ID code corresponding to an "iTV Press" by Mr. Smith.	0x0100 0x0001
Navigator Application Event Record 4 Content	Data
Application ID: See table IV for application ID Code	0x1002

Timestamp: Identifies event time for accessing each screen.	1/1/96 8:01:30 p.m.
Event IDs: See table II for event ID code that identifies an "enter" command by Mr. Smith to invoke this application.	0x0021
Application State ID Code: This shows Mr. Smith accessed the Main Menu	0x01
Navigator Application Event Records 5-6 Content	Data
Application ID: See table IV for application ID Code	0x1002
Timestamp: Identifies event time for accessing each screen. A separate record is created for each activity, with a timestamp showing initiation of each activity. Each record will have the corresponding event and state.	1/1/96 8:02:00 p.m.; 8:03:00 p.m.;
Event IDs: See table II for event ID code that identifies an "enter" command by Mr. Smith to invoke this application.	0x0021 0x0021
Application State ID Codes: This shows Mr. Smith accessed the Movies Sub-Menu and Movie Sub-menu list.	0x03 0x05
Video on Demand Application Event Records 7-9 Content	Data
Application ID: See Application ID table IV (same for each record).	0x1003
Timestamp: Identifies event time for each event recorded by the application. (The day is the same for each record and each time corresponds with the activity identified below).	1/1/96 8:04:00 p.m. 8:50:00 p.m. 8:55:00 p.m.
Event ID: See table II for event ID codes that identify Mr. Smith's play, pause and play commands.	0x0022 0x0024 0x0022
Application State ID Codes: These show Mr. Smith activated this application, played, paused and then played again his selected video.	0x00 0x01 0x00
Cable Application Event Record 10 Content	Data
Application ID: See table IV for application ID Code	0x0011
Timestamp: Identifies event time	1/1/96 9:45:00 p.m.
Event ID: See Global Event ID table II to retrieve code for "power pressed"	0x002

Event Record Upload Cycle

The variably sized event records are collected and then stored in one of two clickstream buffers 42 or 44. Capacity of each of the buffers may be

statically provisioned or the system 20 may addressably download to particular STBs 30 an appropriate buffer 42 or 44 size. A buffer 42 or 44 may be an allocated, contiguous free area of STBs' 30 memory set aside for buffering event records only. Although advanced database techniques like

5 link lists or record pointers could be used, they would increase the application footprint and complexity. Because buffer sizes of about 15 kB would probably accommodate the journaling needs of most applications, advanced database techniques need only be used for larger buffers. Buffers up to 15 kB should allow at least 4 to 8 hours of peak channel "surfing"

10 between uploads (channel surfing typically will generate the most event records). In any event, empirical analysis of network use should determine the optimum buffer size.

Event records are directed to one of the two buffers 42 or 44, although a single or even more buffers could be used with the system 20.

15 Conceivably, the system 20 could also be modified to upload event records in real time; however, that severely increases the possibility of instantaneous overloads in network traffic. Thus, system 20 preferably uses buffers 42 or 44 to buffer collected event records until they are upload.

Event records from a particular STB 30 may be uploaded in a format

20 that assists in their transmission back through the distribution network 52 to the staging server 70. A header record may indicate the time the buffer 42 or 44 was first opened, the number of bytes in the buffer 42 or 44, the originating STB 30 by address, the version of the clickstream kernel 36 which generated the record and the type of data compression used on the

25 following data (if any). This first header record may be of fixed length and uncompressed. Information following "Compression Type" may be compressed to save in transmission bandwidth. Table X below shows this general header format:

Table X: Buffer Header Record	Size
Transaction Code	8 bits
Clickstream Version Number	8 bits
Timestamp	6 bytes
Number of Bytes	8 bits
STB Unique Address Most Significant	16 bits
STB Unique Address Least Significant	32 bits
Compression Type	8 bits

When (1) a buffer 42 or 44 fills, (2) an upload timer event expires or (3) upon command from the staging server 70, the clickstream processor 34 initiates an upload process. During that process the uploading buffer 42 is locked and subsequent event records are routed to and stored in the second 5 buffer 44. When upload of buffer 42 is completed, records continue to buffer 44 until the next upload time, after which buffer 44 locks and records go to buffer 42. This cycle continues to repeat.

Figure 3 shows an upload cycle diagram illustrating one method of evenly distributing increased traffic on the network 52 caused by upload of event records. The clickstream upload cycle consists of several parameters 10 that define a start time and a cycle over which the uploading of data occurs. The "first occurrence" parameter defines a starting time in history from which the cycle runs. The "cycle time" parameter defines the amount of time which elapses between periods of the upload cycle. When a cycle is complete the 15 "upload duration" time starts, and the clickstream processor 34 of each STB 30 will randomize an exact upload time within the upload duration. This timing of uploads will distribute the network load evenly over the entire upload duration period.

An example of the use of these parameters would be to define a 20 period of time every day for STBs 30 within system 20 to upload data. Typically, the system 20 operator may want the data available every morning for analysis. Peak use of broadcast prime time or of interactive services will typically be from 7 p.m. until 12 p.m., during which time no uploads should occur in order to minimize the burden on the network 52. Beginning at 12

p.m., uploads of event records out of a buffer 42 or 44 would begin. In order to have all STBs 30 upload before 8 a.m., the STBs 30 may be divided into upload groups, e.g., 32, with each group uploading over a selected (e.g., 15 minute) period. To achieve this upload cycle, the following parameters are

5 defined in the Figure 3 cycle in table XI:

Table XI: Upload Cycle Parameters	
Parameter	Definition
Cycle_First_Occurance_Start_Time	12:00am Jan 1, 1995 + "X" * 15 minutes. "X" staggers each upload group by 15 minutes; X=number of Groups
Cycle Time	24 hours
Upload Duration	15 minutes

A total of four upload cycles will be defined for each group of STBs 30, which allows for weekly uploads or any other combination of cycles to work around

10 peak network 52 load times.

STBs 30 can be instructed as to their role in uploading by sending from staging server 70 appropriate commands that are handled by the clickstream upload controller 38. For instance, the following commands may be addressed and sent by staging server 70 to a single or group of STBs 30.

15

Table XII: Clickstream Upload Control Commands			
Octet#	Contents		
T 0	Transaction Code MSB = 0x80		
T 1	Transaction Code LSB = 0x10		
0	Clickstream Processor Version Number		
1	Global Flag (b1)	Addressable Flag (b1)	Group Address - Denotes the group of STBs to field this 1 transaction (b5)
2	Collection On/Off Key		Will turn clickstream collection On/Off to a STB or Group of STBs (non-Global only)
3	Perform Upload Now Key		Will perform an upload on command. Will only upload on command if Global Flag is NOT set.

4,	Suppress Upload on Buffer Full	Will keep the STB or Group from uploading when buffer is full. The STB or Group will only upload on it's appointed upload cycle.
5.	Upload_Cycle_Definition	A STB will have 1 to 4 possible upload cycles defined. This will define any one of those cycles.
6.	Cycle First Occurrence Start Time (Total b48)	Year (b8) Defines the time for first upload in a cycle.
7	Cycle First Occurrence Start Time - Month	(b8)
8	Cycle First Occurrence Start Time - Day	(b8)
9	Cycle First Occurrence Start Time - Hour	(b8)
A	Cycle First Occurrence Start Time - Minute	(b8)
B	Cycle First Occurrence Start Time - Second	(b8)
C	Upload Duration (Total b24)	- Hours(0-24) (b8) Defines a duration of time over which the STB randomizes upload start time.
D	Upload Duration	- Minutes(0-59) (b8)
E	Upload Duration	- Seconds(0-59) (b8)
F	Cycle Time (Total b32)	- Days (0-14) (b8) Defines the periodicity (mean time) between uploads.
10	Cycle Time	- Hours(0-24) (b8)
11	Cycle Time	- Minutes(0-59) (b8)
12	Cycle Time	- Seconds(0-59) (b8)

- Depending on how the system is configured, the commands instruct STBs 30 to:
- 1) define the cyclic upload for various groups of or even all STBs 30;
 - 2) require STBs 30 to upload on command/polling control (addressable only);
 - 3) suppress upload when a buffer 42 or 44 fills; or
 - 4) turn on/off event record collection by particular or groups of STBs 30.

Event Record Formatting, Upload and Capture

- After the upload process triggers, each STB 30 typically initiates upload by first locking the buffer 42 or 44 to be uploaded and then
- 10 compressing the contents of that buffer 42 or 44. A number of different compression techniques may be used, however, about 50% compression may be achieved with LZW compression utilities. Such compression substantially reduces the load on network 52 caused by numerous STBs 30

uploading event records. Compressed data is divided into transmission "transactions" or "packets" and packet headers are addressed to indicate packet identification, IP destination address, etc. The actual network connection can be initiated by the operating system for the particular STB

- 5 30. Persons skilled in the art will recognize that the type of and manner of invoking and implementing the network connection will vary depending upon the type of media delivery network over which system 20 is deployed.

For instance, the STB 30 can be configured to insert UDP/IP headers and trailers taken from the RFC 791 or RFC 768 specifications published by the ISO. Each data packet may have UDP/IP protocol built around a Level 1
10 pass-through header, such as shown in Table XIII below:

Table XIII: UDP/IP Protocol for Headers				
IP Header				
IP Version	Header Length	Type of Service	Total Length	
Identification			Flags	Fragment Offset
Time to Live	Protocol		Header Checksum	
Source IP Address				
Destination IP Address				
UDP Header				
Source Port			Destination Port	
Length			Checksum	

- In the embodiment shown in the Figures, the clickstream processor
15 34 will identify a particular VSP -- Video Service Provider, which is an entity connecting to network 52 to distribute services -- like VSP 66 shown in Figure 4B, as the destination of these data packets. All of the data to be uploaded appears as "payload" to the STB 30, the signaling network 52, the network management controller 50, and the event capture process 71 on the
20 staging server 70. After an appropriate header and trailer inserted at the STB 30, the upload data packet may have the format shown in Table XIV:

Table XIV: Clickstream Upload Data Packet	
Octet#	Contents
T 0	Transaction Code MSB = 0x80
T 1	Transaction Code LSB = 0x18
0	Clickstream Processor Version Number
1	Upload Sequence Number
0x02 thr. 0xFA	Clickstream Upload Buffer Data Structure (as shown in Table I and X). The data may be broken up into as many reverse path transactions as necessary to complete data upload.

Providing two buffers 42, 44 allows event record collection to continue during upload. Assuming buffer 42 is being uploaded, if the second buffer

5 44 fills during the upload process, a buffer overrun condition occurs. To account for such an occurrence, the buffer trailer record sent during upload from STBs 30 may denote such an error condition. The structure of the buffer trailer record may take the form as shown in Table XV below and include a time stamp, assigned application identification, length and upload

10 code.

Table XV: Buffer Trailer Record	Size
Timestamp	6 bytes
Assigned Application ID	16 bits
Number Bytes to Follow (length)	8 bits
Upload Status Code	8 bits

These upload status codes identify the stage of the upload process at the time a buffer 42 or 44 overflow occurred. Thus, some possible upload

15 codes could include: upload not used, upload in progress, upload completed but no acknowledgment received, upload completed but only partial acknowledgment received or no upload attempted. This will let the staging server 70 know that STB 30 event records are missing beginning at that time. Also, receiving a buffer overrun record informs the staging server 70

20 that buffer 42 or 44 sizes have not been set appropriately. Buffer 42 or 44

sizes can then be reset and released to the system 20 as an update or released to a particular STB 30 by sending it an appropriate command.

Note that the packetization description above is for one embodiment of the system 20. However, generally, to upload collected event records,
5 STBs 30 can initiate whatever "upstream" data transmission process used by the interactive, cable television or other media delivery system with which the system 20 is used. That process will upload the event records in the appropriate system format.

In any event, for system 20, clickstream data packets are uploaded to
10 the staging server 70 over a slotted-ALOHA (a contention-based standard transport protocol) data transmitter of the STB 30. Data acknowledgments from the staging server 70 are sent; each is addressed to particular STBs 30. The frequency and period of data acknowledgments may be determined by considering network error rates, network packet error rates and causes of
15 those types transmission errors.

Figures 4A and 4B show in greater detail the clickstream data flow through the system 20. Briefly, Figure 4A shows that clickstream packets of event records are transmitted from each STB 30 to the network management controller 50, which acts as a video service provider router. From the
20 network management controller 50, which manages traffic over network 52, packets are forwarded via the network 52, video server 60 and video server control 56 to the staging server 70, which couples to MKIS 100 and analysis engine 110. Thus, event records collected and buffered at STBs 30 are transmitted to the staging server 70 for collection and analysis.

25 Figure 4B shows this process in more detail and also describes an event records capture process 71 at staging server 70.

As noted, once a buffer 42 or 44 fills or the clickstream processor 34 decides to upload data for other reasons (time expiration, low system utilization, commanded upload, etc.), the buffer 42 or 44 will be formatted,
30 compressed and then uploaded through the system 20 to the staging server

70. The upstream data packets may travel from the network management controller 50 across the distribution network 52 to video server 60 through a process called IP ("Internet Protocol") tunneling, which is essentially automatic IP routing based upon information in the packet payload. The same process can be used to route packets through network 52 directly to staging server 70 without going through video server 60. Figure 4B shows that, at video server 60, an L1 pass-through process 63 uses a VSP routing table 67 to associate destination IP addresses with corresponding tags inserted in the received data packets. This process re-directs the data packets to the application server 66 L1 pass-through process 63 by associating the tags with the appropriate listed destination -- here, the application server 66. The L1 pass-through process 63 on application server 66 performs a similar function with the data packets, routing them based on a payload identifier (transaction code or other) to an event record capture ("ECAP") open server process 71 on the staging server 70.

When the ECAP process 71 receives a clickstream data packet, it accepts the data packet and correlates the source address of the data packet with an upload session already in progress with a particular STB 30. If there is currently no upload in progress with that STB 30, then one is considered to be initiated. ECAP process 71 processes the upload of data in accordance with the particular protocol needed for the system 20. After receipt of all clickstream data packets associated with the upload from a particular STB 30, the ECAP process 71 sequences the packets into proper order (particular packets may have arrived out of their original transmission sequence because of transmission delays in network 52), decompresses the packets, eliminates transport overhead (e.g., trailers, headers, etc.) and stores them, such as in a flat file, for later analysis. At the end of a selected period, like 24 hours, the file is closed and a new one is opened, which allows a subsequent merge and parse process to batch process discrete files that cover discrete time periods. Immediately after initiation of and

during the ECAP process 71, an operation log is opened to record information about the initiation and termination of each upload session and any errors.

As shown in Figure 5, staging server 70 will formulate and send a data acknowledgment to each STB 30 engaged in the upload process. One method of doing so is to send acknowledgments as addressable downstream level one pass-through transactions over network 52 to the STB 30. Such data acknowledgments provide redundant error correction because failure to receive them may alert STB 30 to a possible transmission error.

Merging and Parsing

Figures 6A and 6B show an overview of the merging and parsing process and Figure 7 shows sample results following that process. Briefly, the aim of the merge and parse process is to merge each STB 30's event records with various "metadata." "Metadata" refers to (1) programming of virtually any type shown on system 20 including the time and broadcast or cable network providing such programming or (2) interactive applications invoked by subscribers. For instance, metadata includes the following sources of data: EPG broadcast programming schedule data 82, broadcast advertising schedule data 84, local advertising schedule data or session-services advertising schedule data 86 and session-services programming schedule data 88. (Session-services advertising refers to advertising inserted by video server 60 during particular interactive sessions with the subscriber that are the session-services programming).

Collectively, all of this data enters into a merge and parse engine 90 that creates an event timeline 92 for each STB 30. Merge and parse engine 90 may be deployed upon staging server 70 or the MKIS system 100. So deploying merge and parse engine 90 on staging server 70 allows collected event records to be merged and parsed. The resulting event timelines 92 can be sent to MKIS system 100 for further analysis.

Timeline 92 provides a snapshot of activity on a particular STB 30 for a selected period (e.g., 24 hours) or for a selected event -- for instance, a timeline 92 would be created for each STB 30 tuning to a particular show or shows (e.g., a pay per view fight) that may occur over a selected period.

- 5 Timeline 92 is created by merging event records with metadata about programming available over the network for the selected time period.

To merge that data, proper priority must be assigned to data that otherwise may be conflicting. For instance, broadcast advertising data 84 may indicate that a certain national ad was run at Time A. On the other
10 hand, if the system 20 is an interactive system and the interactive server provided a targeted advertisement ("ad") also at Time A, as indicated by session-services advertising data 86, that targeted ad was inserted over the national ad at Time A. Thus, by assigning session-services advertising data 86 a priority higher than national broadcast advertising data 84, the merge
15 and parse engine 90 is able to create an accurate timeline 92 of programming delivered to a particular STB 30. Similarly, even a traditional cable or wireless cable network requires priority assignments. Typically, local cable operators typically are allowed to insert local ads over certain national ads (assuming they can sell that local ad time).

- 20 Figure 6B depicts such priority assignments. Figure 6B shows several sources of data, such as EPG metadata, National and Local Insert ad metadata and Interactive Sessions metadata. EPG metadata is usually very broad -- for instance, showing a football game on channel 1 from 1:00 to 4:00 p.m. Thus, EPG metadata is assigned a priority lower than that of
25 national ad metadata because a particular national ad will be overlayed into a particular time slot broadly defined by the EPG. In turn, local insert ad metadata trumps national ad metadata because the national ad metadata may not account for situations where a local network or affiliate inserts a local ad over the national ad scheduled for a particular timeslot. Finally,
30 interactive sessions metadata, which reflects subscriber selections, has the

highest priority as it shows the subscriber stopped watching a particular channel and instead invoked an interactive session.

Applying these priority rules produces a timeline 94 for each subscriber. Additional filtering criteria 94 are applied by the merge and
5 parse engine 90 in order to generate a further refined timeline 94, as depicted in Figure 6A. For example, event records may include such highly granular and specific information as the number of volume ups or channel ups that a particular subscriber entered. One set of filtering criteria 94 may ensure that the timeline 92 includes only channels that were viewed for
10 more than a threshold (e.g., 15 seconds) time period. This eliminates any very fast channel changes made by the subscribers, thereby simplifying the event timeline 92 because event records that do not meet the criteria 94 are filtered out of the event timeline 92.

Merge and parse engine 90 also may apply other criteria to the
15 filtered timeline 94 (or the original timeline 92), as shown in Figure 6. Specifically, advertisers may wish to apply "view" and "watch" criteria 96. This criteria 96 will identify those programs and advertisements that are "viewed" by subscribers for less than a certain threshold amount of time. Programming seen by subscribers for more than that threshold, would be
20 identified as "watched" programming. For example, for a 30 second ad, the threshold might be 15 seconds. If a subscriber was tuned to a channel displaying that ad for less than 15 seconds he would be deemed to have simply "viewed" that ad; on the other hand, if the subscriber was tuned to the channel carrying that ad for 25 seconds of the ad's length, he would be
25 deemed to have "watched" it. This criteria 96 allows system 20 operators to charge more for "watched" ads versus those that are merely "viewed." Similar criteria can be applied against programming in order to more accurately gauge ratings. Thus, for a 30 minute program, if a user was
30 tuned to that program for less than 10 minutes, the view and watch criteria 96 may decide that the program was only "viewed." In any event, applying

the view and watch criteria 96, merge and parse engine 90 creates "view" and "watch" lists 98 that are useful for the system 20 operator and advertisers who contract with system 20 operator.

5 Note also that other criteria than simply how much time a tuned to a particular channel may be included in the view and watch criteria 96. For instance another criteria may be volume level. If a viewer was tuned to a channel for the full thirty second length of an ad but hit the mute button or changed the volume below a certain threshold for that ad, view and watch criteria 96 may classify that ad as a "viewed" ad.

10 Generally, merging and parsing should be done on discrete segments of data, such as 24 hour segments, as soon as possible in order to minimize the occurrence of un-resolved events. In other words, discrete events are simply pieces of the entire picture. To analyze only several hours of clickstream event data would not allow determination of such things as
15 programming "watched" versus "viewed."

Figure 7 shows a sample merge of event records or clickstream data 80, EPG data 82 from Prevue or a similar service and broadcast advertising data 84 that creates a clickstream timeline 92, which shows both the channels selected by a subscriber and the content displayed on those
20 channels while the subscriber watched them.

A timeline 94 for each STB 30 is built and uploaded by staging server 70 to the MKIS database 100 or a third party analysis engine and database 110, either of which may store demographics and be used to run queries against the event timelines 94 and those demographics. Combining the
25 timelines 94 with demographics information allows for even more detailed and granular information about subscribers and their viewing habits. For instance, consider the following examples:

- Example 1: Widget Co. has ten different advertisements that it has been running on system 20. Widget Co. wishes to know
30 whether subscribers are "viewing" or "watching" particular ads.

Because of the detailed information captured by the system 20 of the present invention, a query can be formulated to determine (a) which subscribers "watched" particular 30 second advertisements for greater than 15 seconds versus (b) which subscribers simply "viewed" the ad, for less than 15 seconds.

- Example 2: When event timelines 94 (or view and watch lists 98) are loaded into MKIS 100 or analysis engine 110, the same query can be run for a particular demographic group. For instance, Widget Co. wishes to know which particular ads its primary customer base, baby boomers between ages 40 and 50 and with income over \$50,000 per year, "watched" versus "viewed" their advertisements.

Obviously, the system 20 can also be modified to target ads to particular demographic households based on feedback from parsed and merged data. Then, event records occurring after those targeted ads are broadcast over system 20 can be checked to determine whether the particular demographic market targeted watched or viewed the advertisement.

The foregoing is provided to explain and disclose preferred embodiments of the present invention, modifications to which may be made that still fall within the following claims. For instance, the architecture and programming of the system may be modified. Or, a variety of different manufacturers' servers, set top boxes or databases may be configured in order to implement the system. The particular identification codes and allocated sizes show in the tables and described herein may also be greatly modified. Further modifications and adaptations to the described embodiments will be apparent to those skilled in the art and may be made without departing from the scope or spirit of the invention and the following claims.

What is claimed is:

- 1 1. A method for collecting information about viewing habits of
2 subscribers to a media delivery network for delivering programming to
3 numerous set top boxes, each capable of supporting different applications
4 invoked and controlled by subscriber commands, the method comprising the
5 steps of:
 - 6 a) programming each application to identify selected
7 subscriber commands of interest;
 - 8 b) determining an application identifier corresponding to a
9 particular application to which a selected command is
10 addressed; and
 - 11 c) creating an event record comprising:
 - 12 (1) the application identifier;
 - 13 (2) an identification code corresponding to the
14 selected command; and
 - 15 (3) a time stamp.
- 1 2. A method according to claim 1 further comprising the step of
2 accessing a table in order to determine the identification code for the
3 selected command.
- 1 3. A method according to claim 2 further comprising the step of
2 accessing a table in order to determine the application identifier.
- 1 4. A method according to claim 2 further comprising the steps of
2 repeating steps a through c to collect a plurality of event records and
3 buffering the plurality of event records.
- 1 5. A method according to claim 4 further comprising the step of
2 forwarding the plurality of event records to a merge processor.

1 6. A method according to claim 5 further comprising the step of
2 coupling to the merge processor a data source selected from the group
3 consisting of: broadcast identification information, interactive application use
4 information, national advertising information and local advertising
5 information.

1 7. The method according to claim 1 in which the selected
2 commands of interest are selected from the group consisting of: channel
3 change commands, volume change commands, VCR commands,
4 application invocation commands and application control commands.

1 8. A system for collecting and processing information about
2 subscribers' selection and use of programming distributed over a media
3 delivery network, the system comprising:
4 a) a merge processor coupled via means for communication to
5 b) a plurality of set top boxes, each comprising a
6 processor for (1) collecting a plurality of event records
7 that describe selected commands from a subscriber to a
8 particular set top box and (2) transmitting event records
9 to the merge processor;
10 c) wherein the merge processor forms an event timeline
11 describing a subscriber's selection of distributed
12 programming for a discrete time period by merging the
13 event records with programming data describing
14 programming available via the media delivery system.

1 9. A system according to claim 8 wherein the programming data
2 comprises data collected from at least two sources selected from the group
3 consisting of: a broadcasting schedule source, a national advertising

4 schedule source, a local advertising schedule source and an interactive
5 application use schedule source.

1 10. A system according to claim 8 wherein each set top box further
2 comprises a plurality of applications capable of being invoked by a
3 subscriber.

1 11. A system according to claim 10 wherein each event record
2 comprises: (1) an application identifier corresponding to the application
3 associated with the recorded event; (2) an event identification code; and (3)
4 a time stamp associated with the initiation of the event.

1 12. A system according to claim 11 wherein each application
2 creates an event record upon detection of selected commands from the
3 subscriber.

1 13. A system according to claim 8 further comprising a buffer for
2 storing the event records before transmission.

1 14. A system according to claim 8 wherein the merge processor
2 forms an event timeline for each of the plurality of set top boxes.

1 15. A system according to claim 14 further comprising an analysis
2 engine for correlating the event timelines with demographics information
3 describing the subscribers.

1 16. A method for journaling information about subscriber use of a
2 media delivery network for delivering programming and a merge processor
3 for analyzing the resulting journaled information, the method comprising the
4 steps of:

- 5 a) collecting information about a plurality of subscribers'
6 use of a media delivery network, the collecting step
7 comprising:
8 i) identifying commands of interest from each
9 subscriber;
10 ii) forming event records that record at least the
11 commands of interest and a time associated with
12 the command;
13 b) transmitting event records to the merge processor;
14 c) merging the event records with data describing the
15 programming delivered over the media network in order
16 to form event timelines, each of which describes the
17 programming selected by a particular subscriber over a
18 discrete time period.

1 17. A method according to claim 16 wherein the identifying step
2 comprises the step of correlating each command of interest with a global
3 table comprising identification codes.

1 18. A method according to claim 16 further comprising the step of
2 filtering the event timelines in order to classify subscribers' viewing patterns
3 into at least two categories.

1 19. A method according to claim 18 wherein the first category
2 comprises programming watched by a subscriber for greater than a selected
3 threshold percent of the total program length.

1 20. A system for determining the viewing habits of subscribers to a
2 media delivery network for delivering programming, the system comprising:

- 3 a) a collector for collecting event records describing subscribers'
- 4 selection and use of programming;
- 5 b) means, coupled to the collector, for communicating event
- 6 records to
- 7 c) a merge processor for processing the event records to form for
- 8 a selected subscriber an event timeline describing the
- 9 programming delivered to a selected subscriber over a
- 10 particular time period via the media delivery network;
- 11 d) means for storing demographics information about selected
- 12 groups of subscribers; and
- 13 e) wherein the merge processor forms a plurality of event
- 14 timelines and correlates the demographics information with the
- 15 event timelines.

1 21. A system according to claim 20 in which the merge processor

2 applies filtering criteria to the event records to determine the programming

3 watched by a subscriber for greater than a selected percent of the

4 programming.

1 22. A system according to claim 21 in which the collector is

2 deployed upon a set top box that is associated with a display device for

3 displaying delivered programming.

1 23. A system according to claim 22 in which the subscriber controls


2 the set top box via a remote device in order to invoke and run a variety of

3 applications and the collector forms event records by:

- 4 a) identifying a code that corresponds to a command of
- 5 interest entered by a selected subscriber; and
- 6 b) storing in a buffer, associated with the collector, an
- 7 event record comprising (1) the code corresponding to
- 8 the command; and (2) a time stamp.

1/10

FIG. 1



2/10




FIG. 2

3/10




FIG. 3





FIG. 4A



6/10




FIG. 5

7/10




FIG. 6A

8/10




FIG. 6B

9/10

CLICKSTREAM DATA 80

	TIMESTAMP	APPLICATION ID	# BYTES TO FOLLOW	APPLICATION SPECIFIC DATA
				EVENT ID CHANNEL ID
EVENT RECORD	3:59:30PM	CABLE APP.	4 BYTES	POWER ON ABC
EVENT RECORD	4:00:00PM	CABLE APP.	4 BYTES	CHANNEL UP NBC
EVENT RECORD	4:04:17PM	CABLE APP.	4 BYTES	CHANNEL UP TBS
EVENT RECORD	4:06:25PM	CABLE APP.	4 BYTES	CHANNEL DWN NBC
EVENT RECORD	4:15:45PM	CABLE APP.	4 BYTES	CHANNEL UP TBS
EVENT RECORD	4:55:45PM	CABLE APP.	4 BYTES	POWER OFF NONE

PREVIEW GUIDE DATA 82

	CONTENT ID	CHANNEL ID	START TIME	END TIME
CONTENT RECORD	NATIONAL NEWS	ABC	3:30:00PM	4:00:00PM
CONTENT RECORD	MURPHY BROWN	NBC	3:59:00PM	4:30:00PM
CONTENT RECORD	SIMPSONS	NBC	4:30:00PM	4:59:00PM
CONTENT RECORD	N.G. EXPLORER	TBS	3:05:00PM	4:05:00PM
CONTENT RECORD	ANDY GRIFFITH	TBS	4:05:00PM	4:35:00PM
CONTENT RECORD	NBA BASKETBALL	TBS	4:35:00PM	6:05:00PM

BROADCAST ADVERTISING DATA 84

	CONTENT ID	CHANNEL ID	START TIME	END TIME
CONTENT RECORD	COCA COLA #10	NBC	4:00:30PM	4:01:00PM
CONTENT RECORD	VISA #2	NBC	4:01:00PM	4:01:30PM
CONTENT RECORD	DELTA #1	TBS	4:03:30PM	4:04:00PM
CONTENT RECORD	DELTA #3	TBS	4:04:00PM	4:04:30PM
CONTENT RECORD	VISA #23	TBS	4:04:30PM	4:05:00PM

PARSE AND
MERGE
DATA

CONTINUED ON
FIG. 7B

10/10

CLICKSTREAM TIMELINE 92

FIG. 7B

EVENT RECORD	TIMESTAMP	APP. ID	#BYTES TO FOLLOW	APPLICATION SPECIFIC DATA		
				EVENT ID	CHANNEL	ID CONTENT ID
EVENT RECORD	3:59:30PM	CABLE APP.	6 BYTES	POWER ON	ABC	NATIONAL NEWS
EVENT RECORD	4:00:00PM	CABLE APP.	6 BYTES	CHANNEL UP	NBC	MURPHY BROWN
EVENT RECORD	4:00:30PM	CABLE APP.	6 BYTES	CHANGE CONTENT	NBC	COCA COLA #10
EVENT RECORD	4:01:00PM	CABLE APP.	6 BYTES	CHANGE CONTENT	NBC	VISA #2
EVENT RECORD	4:01:30PM	CABLE APP.	6 BYTES	CHANGE CONTENT	NBC	MURPHY BROWN
EVENT RECORD	4:03:17PM	CABLE APP.	6 BYTES	CHANNEL UP	TBS	N.G. EXPLORER
EVENT RECORD	4:03:30PM	CABLE APP.	6 BYTES	CHANGE CONTENT	TBS	DELTA #1
EVENT RECORD	4:04:00PM	CABLE APP.	6 BYTES	CHANGE CONTENT	TBS	DELTA #3
EVENT RECORD	4:04:30PM	CABLE APP.	6 BYTES	CHANGE CONTENT	TBS	VISA #21
EVENT RECORD	4:03:17PM	CABLE APP.	6 BYTES	CHANGE CONTENT	TBS	N.G. EXPLORER
EVENT RECORD	4:05:00PM	CABLE APP.	6 BYTES	CHANGE CONTENT	TBS	ANDY GRIFFITH
EVENT RECORD	4:06:25PM	CABLE APP.	6 BYTES	CHANNEL DWN	NBC	MURPHY BROWN
EVENT RECORD	4:15:45PM	CABLE APP.	6 BYTES	CHANNEL UP	TBS	ANDY GRIFFITH
EVENT RECORD	4:35:00PM	CABLE APP.	6 BYTES	CHANGE CONTENT	TBS	NBA BASKETBALL
EVENT RECORD	4:55:45PM	CABLE APP.	6 BYTES	POWER OFF	NONE	